

CRTS

RP231

ADDENDUM SHEET TO P.C.2
SERVICE MANUAL
R.G.D.
RECORD PLAYER MODEL RP231



A DIVISION OF **STC**

Issued MAY 1965

COMBINED RADIO AND TELEVISION SERVICE LTD

REGENT WORKS, SIDCUP, KENT. Tel: FO0tscray 3333

SERVICE ORGANISATION FOR KB REGENTONE RGD ACE ARGOSY

ALSO PROVINCIAL DEPOT AT

COLLEGE MILTON

EAST KILBRIDE

GLASGOW

EAST KILBRIDE 25101

RP231

Dimensions :

Height —	7½"
Width —	15½"
Depth —	17"
Weight —	14½ lbs.

DESCRIPTION	PART/LOCATION No.
Cabinet Assembly	983/3/21630
Lid Assembly	983/130/21524
Bottom Moulding	983/131/21629
Handle	28/102/14201
Handle Pivots (2 off)	35/286/14150
Cabinet Back	34/98/27037
Moulded Foot, Front (2 off)	28/96/21492
Moulded Foot, Rear (2 off)	28/95/21700
Front Moulding	35/227/2/21639
Badge	21/132/13648
Speaker Baffle	34/86/21768
Anodised Grille	28/100/13720
Control Escutcheon	35/277/13716
Control Panel	21/131/13717
Name Plate Escutcheon	35/275/13659
Motor Board	983/4/51/21764
Knob Assembly (2 off)	983/60/01112
Garrard Auto Changer	37/36/1/19384
Motor	37/36/1/M/19657
P.U. Cartridge (Garrard GC8M)	GC8M/19642
Stylus L.P.	GC8M/LP/19664
Stylus 78	GC8M/78/19665
Speaker (7" x 3½" Impedance 25 ohms)	11/159/03114
Back Support Rail	33/256/21635
Hinges (2 off)	28/107/1/14194
Hinge Platform (2 off)	35/272/14174
Catch (2 off)	28/108/1/14192
Catch Platform (2 off)	35/270/14191
Tone Control 500K Lin.	9/258/02105
Volume Control with ON/OFF switch 5 Meg. Log	9/259/02090

Chassis Removal Instructions

Remove chassis cover (3 screws) and cabinet base by removing the four feet. Unsolder the screened amplifier input lead from the tag panel on the underside of the gram deck. Remove cleats holding mains cable to cabinet. Remove the four nuts holding the baffle and front moulding to metal side pieces. The baffle complete with chassis and speaker can then be withdrawn. The printed circuit may then be detached from the metalwork by removing fixing screws (2 off) and the two screws securing the heat sinks.

N.B. Do not operate amplifier without heat sinks secured to the aluminium plate.